

# DEEPMATIC 40

## POMPA AUTOMATICA

Pompa Sommersa per autoclave e svuotamento automatico di acque pulite. Camicia esterna INOX e polipropilene rinforzato in fibra di vetro 30%. Tenuta meccanica in nitrile/ceramica/carbonio, giranti in PPO, classe di funzionamento continuo. Profondità max 7 mt.

Completa di galleggiante e 10 metri di cavo con spina schuko.


Motore termoprotetto dal surriscaldamento  
Albero Motore rivestito in CERAMICA a protezione della tenuta e del cuscinetto

### CODIFICAZIONE

F R A D M 4 0

OPTIONAL: \_\_\_\_\_  
Comando Elettronico Separato  
Separated Pump Control

- 1: AQUAMATIC
- 2: RE-START 2HP
- 3: HYDROGEL 2HP
- 4: HYDROMATIC 2HP



**4,0 bar**

## AUTOMATIC PUMP

Submersible Pump for boosting. Externally fitted

floating switch for the automatic clean water emptying.


Stainless steel motor shell and 30% fiber glass reinforced polypropylene, nitrile/carbon/ceramic

mechanical seal, PPO impellers, continuous duty.

Compact and easy to install, complete with 10 meters cable and euro plug. MAX DEEP 7 METERS

Thermal protected motor

Ceramic coating of the motor shaft to protect the bearing and mechanical seal



▽  
**7m**

connessione idraulica 1"

1" hydraulic connection

Ø 153 x 385 mm

8,5 kg peso/weight



385

